

盤面式直流毫安電流, 直流電壓產生器 (DC CURRENT(VOLTAGE) CALIBRATOR PANEL METER)

MODEL
MDFG-VR



■特點(FEATURES)

- 精確度0.1%滿刻度±1位數(Accuracy 0.1% F.S.±1digit)
- 顯示範圍-1999~+1999位數(Display range-1999 to +1999 digit)
- 可顯示與產生精密直流毫安電流,直流電壓(Calibrator for DCmA and DCV)
- 盤面電位計直接設定,操作簡易(Potentiometer setting output by front panel,easy to operate)
- 尺寸小,穩定性高(Dimension small and High stability)

1.MODEL:MDFG-VR□ - [min] - [max] - [unit]
(選購型號) (顯示範圍與單位)
(最小值)-(最大值) -(單位)

NO	Analog output	NO	Analog output	NO	Analog output
A	DC0~19.99mV	E	DC0~10.00V	I	DC4~20mA
B	DC0~199.9mV	F	DC0~1.000mA	O	SPECIFIED
C	DC0~1.999V	G	DC0~10.00mA		
D	DC1~5.00V	H	DC0~19.99mA		

2.SPECIFICATION (主要規格)

- Aux.power supper (輔助電源) : AC110V & 220V±20%(50/60Hz)
- Accuracy (精確度) (23±5°C) : 0.1% F.S.±1 digit
- Display (顯示幕) : Red high efficiency LEDs high 14.22mm(0.56")
- Response time (輸出反應時間) : <50ms (0~90% setting)
- Output drive capability (輸出負載能力) : <10mA for voltage mode
<10V for current mode
- Output ripple (p-p) (輸出之漣波) : <0.1% F.S.
- Zero (offset) range (歸零調整範圍) : 0~±100 digit (display)
0~±5% F.S. (analog output)
- Span (scale) range (最大值調整範圍) : 0~±200 digit (display)
0~±10% F.S.(analog output)
- Temp. coefficient (溫度係數) : 50ppm/°C (0~50°C)
- Isolation (隔離特性) : VR/Power/Case
- Insulation Resistance (絕緣阻抗) : >100Mohm with 500VDC
- Dielectric strength (絕緣耐壓能力) : 2KVac/1 min. (input/output/power)
1600 Vdc(input/output)
- Operating condition (使用環境條件) : 0~50°C (20 to 90% RH non-condensed)
- Storage condition (存放環境條件) : 0~70°C (20 to 90% RH non-condensed)
- CE EMC Certification (CE認證) : EN 55022:1998/A1:2000 Class A
EN 61000-3-2:2000
EN 61000-3-3:1995/A1:2001
EN 55024:1998/A1:2001

3.OUTSIDE DIMENSION AND CONNECTION DIAGRAM (外型尺寸與開孔尺寸與配線圖)

