

微電腦型RS-485顯示電錶(24X48mm/48x96mm) (MICROPROCESS RS-485 DISPLAY METER)(24X48mm/48x96mm)

**MODEL
MMX-RS**



特點(FEATURES)

5位數RS-485顯示電錶(5 digit RS-485 display meter)
顯示範圍-19999-99999位數(Readout range form -19999 to 99999 digit)
通訊協議Modbus RTU模式(Modbus RTU mode for RS-485 protocol)
寬範圍交直流兩用電源設計(Wide input range for auxiliary power)
尺寸小,穩定性高(Dimension small and High stability)

1.MODEL:MMX-RS- (選購型號)

NO	Display	NO	Case Size	NO	Aux. Power
1	One-display	1	24x48mm	A	AC/DC18-60V
2	Two-display	2	48x96mm	B	AC/DC90-260V
Two-display only 48x96mm					Less 3VA for AC/DC input

2.SPECIFICATION (主要規格)

Readout range (顯示範圍)	: -19999~99999 digit
RS-485 baud rate (傳輸速率)	: 19200/9600/4800/2400 selective
RS-485 address (通訊位址)	: "01"-"FF"
RS-485 protocol (通訊協議)	: Modbus RTU mode
Display (顯示幕)	: Red high efficiency LEDs high 10.16 mm (0.4") (MMX-RS-11X) Red high efficiency LEDs high 20.32 mm (0.8") (MMX-RS-12X) Red high efficiency LEDs high 10.16 mm (0.4")x2 (MMX-RS-22X)
Parameter setting (參數設定方式)	: Touch switches
Memory mode (記憶方式)	: Non-volatile E ² PROM memory
Dielectric strength (絕緣耐壓能力)	: 2KVac/1 min. (input/power)
Operating condition (使用環境條件)	: 0-50 (20 to 90% RH non-condensed)
Storage condition (存放環境條件)	: 0-70 (20 to 90% RH non-condensed)
CE EMC Certification (CE認證)	: EN 55022:1998/A1:2000 Class A EN 61000-3-2:2000 EN 61000-3-3:1995/A1:2001 EN 55024:1998/A1:2001

3.OUTSIDE DIMENSION AND CONNECTION DIAGRAM (外型尺寸與開孔尺寸與配線圖)

